

# TouchNTuff®

ADVANCED PRODUCT & WORKER PROTECTION

## 92-500

Versatile Powdered  
Disposable Nitrile Glove

NBR

Nitrile

## Proven splash resistance against hazardous chemicals\*

- Permits easy donning and moisture absorption
- Three times the puncture resistance of latex or PVC disposables
- Enhanced chemical splash protection for longer periods
- Offers superior comfort due to proprietary nitrile formulation
- Delivers strong grip in wet or dry conditions



### Industries

- Agriculture
- Automotive and transportation
- Building and construction
- Chemical and Petrochemical
- Electronics
- First Responders
- Food Processing
- General Industry
- Janitorial/Sanitation
- Metal Fabrication  
(includes glass & non-metallics)
- Pharmaceutical

### Applications

- Chemical handling
- Emergency response (EMS and EMT)
- Handling of cytostatics
- Handling oils, acids, caustics and alcohols
- Laboratory analysis
- Maintenance work
- Painting and spraying
- Printing
- Protection from blood and other bodily fluids
- Small parts assembly and handling

[WWW.ANSELL.COM](http://WWW.ANSELL.COM)

**Ansell**

#### TECHNICAL DATA SHEET: PRODUCT INFORMATION:

<b>Material</b>	Nitrile
<b>Color</b>	Green
<b>Glove Design</b>	Ambidextrous, Powdered, Textured Fingers
<b>Cuff</b>	Beaded Cuff
<b>Manufacturing/QMS Audit Standards</b>	ISO 9001
<b>Regulatory/Standards Compliance</b>	EN 420, EN 374/1,2,3, ASTM D36119, FDA 21 CFR 177-2600, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities
<b>Packaging</b>	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Sri Lanka
<b>User Needs Segment</b>	Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times.

#### PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES				TESTING METHOD
	S	M	L	XL	
SIZE	6½-7	7½-8	8½-9	9½-10	ASTM D3767/EN 420
Length (mm)	240	240	240	240	
Average Palm Width (mm)	85	95	106	110	

Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm: 0.12) / (mils: 4.7)	ASTM D3767/EN 420

	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength	> 14 Mpa	> 14 Mpa	ASTM D 412-06a
Elongation at Break (%)	> 500	> 400	ASTM D 412-06a
Force at break (N)	> 6	> 6	EN 455-2

#### ORDERING INFORMATION:

SIZE	S	M	L	XL
	6½-7	7½-8	8½-9	9½-10
ASPN	588198	588199	588200	588201

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

\*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa**  
Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
+32 2 528 74 00  
+32 2 528 74 01

**Asia Pacific**  
Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jalan Teknokrat 6  
63000 Cyberjaya  
Selangor, Malaysia  
T: +60 3 83106688  
F: +60 3 8318 6699

**North America**  
Ansell Healthcare Products LLC  
111 Wood Avenue South  
Suite 210  
Iselin, NJ 08830, USA  
+1 800 800 0444  
+1 800 800 0445

**Latin America & Caribbean**  
Ansell Brazil Ltda.  
Rua das Figueiras 474 - 4º Andar  
Bairro Jardim  
SP 09080-300 Santo André  
Brazil  
CNPJ: 03.496.778/0001-21  
+55 11 3356 3100

**Australia**  
Ansell Limited  
Level 3, 678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
+61 1800 337 041  
+61 1800 803 578

**Russia**  
Анселл РУС  
123610 Россия, Москва  
Краснопресненская  
Наб. 12, п.3, оф. 1304А  
Тел. +7 495 258 13 16

Regulatory Compliance

EAC CE 0493

TP TC 019/2011

Performance Standards



EN 374

EN 374

**Ansell**