



## KRATOS HELIXON-S WIRE ROPE RETRACTABLE FALL ARREST

**SKU:** N/A

**Stock:** Available to Order (2-3 Days) Ordered in and delivered within 2-3 days.

| SKU       | Stock Status                                                                           | Stock Quantity | Length | Price          |
|-----------|----------------------------------------------------------------------------------------|----------------|--------|----------------|
| FA2040210 | Available to Order (2-3 Days)<br>Ordered in and delivered within 2-3 days.             |                | 10.0m  | £357.57 ex VAT |
| FA2040215 | Available to Order (2-3 Days)<br>Ordered in and delivered within 2-3 days.             |                | 15.0m  | £437.46 ex VAT |
| FA2040220 | Out of stock<br>Currently unavailable. This item will be delivered when stock arrives. | 0              | 20.0m  | £497.22 ex VAT |

### Robust & durable polymer casing, equipped with:

a carrying handle,  
a wire rope-cleaning brush,  
a window, that can be easily removed for reaching the internal mechanism, in order to inspect it without totally opening the casing.

### Comes with Galvanized Steel Wire Rope of diam 4.8 mm, having:

a connector ref. FA 50 203 20 with load indicator,  
a gripping handle,  
an external energy absorber.

- Internal braking mechanism to reduce the fall arrest force to less than 6 kN.
- Swivel and FA 50 101 17 connector at anchorage end.

**Compliance:** EN 360:2002.

Minimum breaking strength > 12 kN.

**Approved for a user with a max. weight of 140 kg in vertical use and in horizontal use.**

**HS Code:** 8428 9090

Delivered with a cord (FA 20 904 15) for guiding the winding back of the wire rope.